



## H125 Specifications

Model #	H125	H125	H125	H125	H125	H125	H125
	32-10	48	64	96	128	160	192
<b>Factory Regeneration Settings</b>							
Backwash Minutes	8	8	8	8	8	8	8
Backwash Gallons	18	18	34	34	42	60	60
Brine/Rinse Minutes	60	60	60	60	60	60	60
Brine/Rinse Gallons	24	24	41	47	66	85	114
Backwash Minutes	8	8	8	8	8	8	8
Backwash Gallons	18	18	34	34	42	60	60
Fast Rinse Minutes	4	4	4	4	4	4	4
Fast Rinse Gallons	9	9	17	17	21	30	30
<b>Total Regeneration Gallons</b>	<b>68</b>	<b>68</b>	<b>125</b>	<b>131</b>	<b>172</b>	<b>235</b>	<b>264</b>

Refill LBS of salt	Lbs.	Lbs.	Lbs.	Lbs.	Lbs.	Lbs.	Lbs.
Low Salt	6	9	12	18	24	30	36
Medium Salt	<b>10</b>	<b>15</b>	<b>20</b>	<b>30</b>	<b>40</b>	<b>50</b>	<b>60</b>
High Salt	15	22.5	30	45	60	75	90

Capacity	Grains	Grains	Grains	Grains	Grains	Grains	Grains
Low Salt	19,000	28,500	38,000	57,000	76,000	95,000	114,000
Medium Salt	<b>28,000</b>	<b>42,000</b>	<b>56,000</b>	<b>84,000</b>	<b>112,000</b>	<b>140,000</b>	<b>168,000</b>
High Salt	32,000	48,000	64,000	96,000	128,000	160,000	192,000

Service Flow Rates	GPM	GPM	GPM	GPM	GPM	GPM	GPM
Continuous @ 15 psi	22	19	25	24	25	27	26
Peak @ 25 psi	31	28	34	33	34	35	34

Flint Under bed (lbs.)	14	14	40	40	45	50	75
High Capacity Resin (cu.ft.)	1	1.5	2	3	4	5	6
Resin Tank Size	10x44	10x54	13x54	14x65	16x65	18x65	18x65
Recommended Brine Tank	18X40	18X40	18x40	18x40	24x41	24X50	24x50
Brine Line Size	3/8"	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"
DLFC (gpm)	2.2	2.2	4.2	4.2	5.3	7.5	7.5
BLFC (gpm)	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Injector Size	D-Red	E-WHITE	G-Yellow	H-Green	I-Orange	J-L Blue	K-L Green